














CERTIFICATION AND CLASSIFICATION		Force
Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering
CE certification		 yes
Classification	ISO 10874 (EN 685)	 Residential: 23  Commercial: 33
TECHNICAL CHARACTERISTICS		Force
Extreme protection PUR reinforcement		yes
Total thickness	ISO 24346 (EN 428)	 2,50 mm
Wear layer thickness	ISO 24340 (EN 429)	 0,60 mm
Total weight	ISO 23997 (EN 430)	 2,5 kg/m ²
Form of delivery - Rolls	ISO 24341 (EN 426)	 30 lm (15-30lm) x 2,5/3m 25 lm (15-25lm) x 3,5m 22 lm (15-22lm) x 4m
Wear layer binder content		Type I
TECHNICAL PERFORMANCES		Force
Dimensional stability	ISO 23999 (EN 434)	 Requirement by standard: < 0,4 % Tarkett result: ≤ 10,011 %
Reaction to fire	EN 13501-1	 Bfl - s1
Residual indentation	ISO 24343-1 (EN 433)	 ≤ 0,20 mm
Impact sound reduction	ISO 717/2	 10 dB
Underfloor heating		 Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance		Does not contribute to infection spreading
Castor chair test	ISO 4918 (EN 425)	 Excellent
Light fastness	ISO 105 B02 - Method 3	≥ 6
Thermal resistance	EN 12524	0,03-0,04 m ² K/W
Static electrical propensity	EN 1815	≤ 2 kV (antistatic)



	 100% recycled by 100% recyclable	 EN 13893	 EN 1815		Manufactured by: Tarkett d.o.o. Bačka Palanka Industrijska zona 14 21400 Bačka Palanka SERBIA
---	--	--	---	---	---