

Vebe Floorcoverings bv Inslag 12, 8281 JV P.O. Box 11, 8280 AA Genemuiden, The Netherlands W

(+31) 88 825 11 00

F (+31) 38 385 61 87 Е info@vebe.net

т

www.vebe.net

lanufacturing process	Tufted		ISO 2424
Gauge	1/8" Cutpile		
Pile yarn composition	100% PP		
rimary backing	Woven		
Backing	GC		ISO 2424
Pile weight	380 g/m <sup>2</sup>		
fotal weight	1060 g/m²	+/- 10%	ISO 8543
Pile height	5,0 mm		ISO 1765
fotal height	7,0 mm	+/- 10%	ISO 1765
Tufts per m²	120900		
Colour fastness to light	> 7		ISO 105-B02
Roll width	100 cm, 133 cm, 200 cm, 400 cm		
Roll length	30		
Application	Landscaping		

## Floorsymbols



2016-12-21

Vebe Floorcoverings b.v. products are to be installed in full accordance with Vebe installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Vebe products should only be used as floorcoverings. Note: Vebe Floorcoverings b.v. reserves the right to adapt this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site.

In the area of office chairs we recommend to use mats made of polycarbonate. This extends the life of your carpet.

During normal use, maintenance and cleaning procedures, the mentioned products will be guaranteed for a period of 1 year on the carpet-properties and UV-resistance. Due to sunshine (UV-radiation) and / or moisture the color of the fibers will change in time. This is usual for the mentioned products.

With artificial grass, weather conditions may cause a shrinkage of  $\pm$  2%.

