

TECHNICAL SPECIFICATIONS

Product type	LVT	Installation	Glue-down
Overall thickness	2.5mm	Bevel	Cut bevel on 4 sides
Wear layer	0.5mm	Finish	UV coating

CLASS OF USE AND WARRANTY

Domestic	23 Heavy	Commercial	33 Heavy
Domestic Warranty	Lifetime Limited	Commercial Warranty	15 Years Limited

CERTIFICATIONS

CE Marking	Compliant	GreenGuard Gold	Compliant
IAC Gold	Compliant		

CHEMICAL PROPERTIES

Norm	Item	Test method	Requirement	Result
EN 14041	Emissions	EN 717-1	≤0.12 mg/m3	Compliant
Decret No.2011-321	Emissions	ISO 16000	TVOC<1000µg/m3	Compliant
Prop 65	Orthophthalates	Spectrometry	ND	Compliant
CPSIA & Prop 65	Ortho-Phthalates	CPSC-CH-C-1001-09.4	N.D.	Compliant
REACH	SVHC	Spectrometry, chromatography	≤0.1% (w/w)	Compliant

PHYSICAL PROPERTIES

Norm	Item	Test Method	Requirement	Result
ISO 10582	Length tolerance	ISO 24342	≤0.15% of nominal L up to max 0.5mm	Compliant
	Width tolerance	ISO 24342	≤0.1% of nominal L up to max 0.5mm	Compliant
	Thickness tolerance	ISO 24346	+0.13mm/-0.1mm	Compliant
	Wear layer thickness	ISO 24340	+13%/-10%	Compliant
	Dimensional stability	ISO 23999	ΔW/ΔL ≤ 0.25%	Compliant
	Curling	ISO 23999	≤2mm	Compliant
	Residual Indentation	ISO 24343-1	≤0.1mm	Compliant
	Castor chair	ISO 4918	Slight change only	Compliant
	Light fastness (Blue wool)	ISO 105-B02:2014 Method 3A	≥Grade 6	Compliant
		ASTM F1515	△E ≤8	Compliant
EN 16511	Martindale (Gloss retention)	EN 16094	≤MSR-A3	Compliant
	Martindale (Micro-scratch)	EN 16094	≤MSR-B3	Compliant
	Furniture leg	EN ISO 16581	No visible change	Compliant
	Resistance to staining	EN 438-2	Group 1 and 2: Grade 5 Group 3: Grade 4	Compliant
EN 14041	Thermal resistance (R)	EN 12664/ASTM C518	NA	Compliant
	Slip resistance	EN 13893	≥0.3	Compliant
	Reaction to fire	EN 13501-1	Bfl-s1	Compliant
Others	Slip resistance	DIN 51130/DIN EN 16165 Annex P	≥R9	Compliant

LEED SCORECARD

How our products fit into LEED v4:

Credit Type	Points	Criteria	Product Contribution
LEED BD+C and ID+C	EQ Credit: Low-Emitting Materials 1-3 points	Option 1. Product has been tested according to California Department of Public Health (CDPH) Standard Method v1.2-2017 and complies with the VOC limits in Table 4-1 of the method. Additionally, the range of total VOCs after 14 days (336 hours) was measured as specified in the CDPH Standard Method v1.2 and is reported (TVOC ranges: 0.5 mg/m3 or less, between 0.5 and 5 mg/m3, or 5 mg/m3 or more). Option 2. Product has been tested according to EN 16516:2017 and complies with the LCI values from Table 1 of the German AgBB Testing and Evaluation Scheme (2015) and a formaldehyde limit of 10 micrograms per cubic meter. Additionally, the range of total VOCs after 28 days was measured as specified in EN 16516 and reported (TVOC ranges: 0.5 mg/m3 or less, between 0.5 and 5 mg/m3, or 5 mg/m3 or more).	CFL LVT products are GreenGuard Gold certified.
MR Credit: Building Product Disclosure and Optimization – Material Ingredients	1 point	Option 1. Material Ingredient Optimization International Alternative Compliance Path – REACH Optimization (value at 100% of cost or 1 product). End use products and materials have fully inventoried chemical ingredients to 100 ppm and assess each substance against the Authorization List – Annex XIV, the Restriction list – Annex XVII and the SVHC candidate list, (the version in effect June 2013,) proving that no such substance is included in the product. If the product contains no ingredients listed on the REACH Authorization, Restriction, and Candidate list.	CFL LVT products are REACH compliant.

WELL SCORECARD

The WELL Building Standard is founded on the understanding that facets of our environment interact with personal, genetic and behavioral factors to shape our overall health and well-being. By compiling leading practices in building design and management and referencing existing standards and best practice guidelines set by governmental and professional organizations, WELL works to harmonize and clarify existing thresholds and requirements.

Facet	Feature	Part	Requirements	Concept score	How our product contribute to obtain WELL level certification
-------	---------	------	--------------	---------------	---

AIR

01. Air quality standards	1. Standards For Volatile Substances	<p>The following conditions are met:</p> <ul style="list-style-type: none"> a. Formaldehyde levels less than 27ppb (0.027ppm) b. Total volatile organic compounds less than 500ug/m³ (0.5mg/m³) 	PRECONDITION	<ul style="list-style-type: none"> a. Formaldehyde emission are less than 27 ppb. b. The total volatile organic compounds are less than 0.5mg/m³.
04. VOC Reduction	1. Interior Paints and Coatings	<p>The VOC limits of newly applied paints and coating meet one of the following requirements:</p> <ul style="list-style-type: none"> a. 100% of installed products meet California Air Resources Board (CARB) 2007, Suggested Control Measure (SCM) for Architectural Coatings, or South Coast Air Quality Management District (SCAQMD) Rule 1113, effective June 3, 2011 for VOC content. b. At minimum 90%, by volume, meet the California Department of Public Health (CDPH) Standard Method v1.1-2010 for VOC emissions 	PRECONDITION	<ul style="list-style-type: none"> a. The VOC limits for California Air Resources Board (CARB) are less than 0.11ppm. b. Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHBL Standard Method v1.1-2010). <p>The product is GreenGuard Gold certified</p>
3. Flooring		<p>The VOC emissions of all newly installed flooring must meet all limits set by the following, as applicable:</p> <ul style="list-style-type: none"> a. California Department of Public Health (CDPH) Standard Method v1.1-2010. 	PRECONDITION	<p>Conforms to the CDPH/EHBL Standard Method v1.1-2010 (California Section 01350), effective January 1, 2012, for the school classroom and private office parameters when modeled as Flooring.</p> <p>The product is GreenGuard Gold certified</p>
11. Fundamental Material Safety	1. Asbestos and Lead Restriction	<p>All newly-installed building materials meet the following materials composition requirements:</p> <ul style="list-style-type: none"> a. No asbestos. b. Not more than 100 ppm (by weight) added lead. 	PRECONDITION	<ul style="list-style-type: none"> a. No asbestos b. The product contain less than 100 ppm.
	2. Lead Abatement	<p>For repair, renovation or painting on buildings constructed prior to any applicable laws banning or restricting lead paint, lead evaluation and abatement.</p>	PRECONDITION	The product contain less than 90 ppm.
	3. Asbestos Abatement	<p>To reduce hazards in buildings constructed prior to any applicable laws banning or restricting asbestos, the following testing, evaluation and abatement.</p>	PRECONDITION	The product contain less than 90 ppm.
25. Toxic Material Reduction	2. Flame Retardant Limitation	<p>Halogenated flame retardants are limited in the following components to 0.01% (100 ppm) to the extent allowable by local code:</p> <ul style="list-style-type: none"> a. Window and waterproofing membranes, door and window frames and siding. b. Flooring, ceiling tiles and wall coverings. c. Piping and electrical cables, conduits and junction boxes. d. Sound and thermal insulation. e. Upholstered furniture and furnishings, textiles and fabrics. 	OPTIMIZATION	The product don't contain halogenated flame retardants
	3. Phthalate (Plasticizers) Limitation	<p>DEHP, DBP, BBP, DINP, DIDP or DNOP (often found in polyvinyl chloride [PVC]) are limited in the following components to 0.01% (100 ppm):</p> <ul style="list-style-type: none"> a. Flooring, including resilient and hard surface flooring and carpet. b. Wall coverings, window blinds and shades, shower curtains, furniture and upholstery. c. Plumbing pipes and moisture barriers. 	OPTIMIZATION	<p>In accordance with US Consumer Product Safety Improvement Act 2008 (CPSIA) (H.R.4040) Title I, Section 108 & California Proposition 65 & Annex XV II item 51&52 of the REACH Regulation (EC) No. 1907/2006 and amendment No. 552/2009, the product contains less than 100ppm.</p>
	5. Urea-Formaldehyde Restriction	<p>Urea-formaldehyde presence is limited in the following components to 100 ppm:</p> <ul style="list-style-type: none"> a. Furniture or any composite wood products. b. Laminating adhesives and resins. c. Thermal insulation. 	OPTIMIZATION	The product contains urea-formaldehyde less than 100ppm.